

NeoGate TB400 – VoIP BRI Gateways (BRI-VoIP)



NeoGate TB400 is a full-featured VoIP gateway. It's used to integrate your PABX to VoIP phone service or extend an ISDN-BRI line of a PBX to a remote site over VoIP.

Specifications

Interface: SIP, BRI

BRI Port: 4 (RJ45)

Protocol: SIP (RFC3261)

DTMF: RFC2833, SIP INFO, In-band

Codec: G.711 A/u-law, G.726, G.729 A, GSM, Speex.

LAN: 1 (10/100Mbps)

Network: DHCP Server, VLAN, Firewall.

Size: 200x140x35mm

Power Supply: AC 100~240V/50~60Hz (DC 12V, 1A)

Environment Conditions

Operation Range: 0° to 50°C, 32° to 122° F

Storage Range: -20° to 65°C, 4° to 149° F

Humidity: 10-90% non-condensing

Features

BRI ports can be used as TE/NT mode

SIP proxy Registrar for IP phones included

LCR (Least Cost Routing)

Simple web based configuration

Easy to integrate

Easy to install

Benefits

1) Cost Savings – Cost-Savings on phone calls via VoIP.

2) Easy to install – IP device with Web based management interface.

3) Easy to integrate

[END]