

## P10/P10P

## **Entry-level office IP phone**

Flyingvoice P10/P10P Entry-Level office IP phone, with 132x64 pixels black and white LCD with backlight, providing users with a clear visual experience. P10/P10P supports 2 SIP accounts, integrated 100M dual network ports, PoE (P10P only) interface to meet the entry-level needs of corporate offices. It supports six conferencing, HD voice, and is easy to install and wall mount, meeting different application scenarios for desktop office and wall mount use. This easy-to-use, cost-effective IP phone can help you improve office efficiency and achieve quality voice communication.











#### All-new Design, Parctical details

P10/P10P adopts a new UI design, with a stylish and simple appearance and a friendly and easy-to-use operating interface, with a new breathing light caller alert, providing users with a more flexible and efficient voice collaboration experience.



#### **HD Voice Quality, Better Calling Experience**

P10/P10P uses advanced echo cancellation technology and intelligent noise cancellation technology to provide users with high-definition voice and achieve better voice calls.



#### Simple installation and easy deployment

P10/P10P with FRPS system and FACS platform for unified, fast and efficient bulk deployment, no need to change the existing IP network wiring, say goodbye to the complex deployment method, greatly reduce the time and labor costs, easy to manage, upgrade and maintain.



#### **High Security, Strong Compatibility**

P10/P10P are well protected by configuration files with AES, SRTP and TLS call encryption, etc.The P1X series IP phones are widely compatible with SIP based devices and PBX platforms such as Asterisk, Broadsoft and 3CX, etc.




- 128\*64px backlit LCD screen
- 2 x 10/100 Mbps Ethernet port
- Supports PoE (P10P only)
- 6-Way conferencing
- 2 SIP accounts
- HD Voice
- RJ9 headset
- Wall mountable
- Opus




# P10(P) Specifications

Phone Features		
LCD Screen	> 128*64px backlit B/W LCD screen > 16 bit depth color	
Function Keys	> 12 Function Keys:home, directory, message, paging, call Hold, Record, mute, headset, transfer, redial, hands-free speakerphone > 4 Soft Keys, 4 Navigate Keys, Volume+/-	
SIP Accounts	> 2 SIP accounts	
Wi-Fi	> No supported	
USB Port	> No supported	
Ethernet Port	> 2*10/100M (adaptive) > Support PoE (P10P only)	
Other Ports	> 1 x Handset port, 1 x RJ9 headset port	
Call Features		
Basic function	> Call hold, mute, DND, redail, auto answer, One-touch speed dial, hotline, SMS, Call forward, call waiting, call transfer (attended/blind), Paging, Voice mail, BLF, Anonymous call, anonymous call rejection, Message waiting indicator(MWI), Hotdesk	
Direct IP Call	> Supported	
Phone book	> 2000 records; Phonebook search/import/export; XML/LDAP remote phonebook; Black list	
Call history	> 60 records; Call history: dialed/received/missed	
6-way conferencing	> Supported	
Audio Features		
HD Voice	> HD handset, HD speaker	
Wideband Codec	> G.722, Opus, AMR-WB(Optional), G.711WB(Optional), G.711(A/u), Ilbc, G.729A/B, G.723, G.726, AMR-NB(Optional)	
DTMF	> In-band, RFC 2833, SIP info	
Network		
Network Safety	> SIP Related Features: - SIP v1 (RFC2543), v2 (RFC3261),NAT Traversal by STUN, - SIP link mode: Proxy mode and peer-to-peer SIP link mode, - Call server redundancy supported > Network Features: - Static IP and DHCP, IPv4 /IPv6, Dual stack IPv4/IPv6, ARP/RARP, DNS A/DNS SRV/DNS NAPTR, - LLDP/CDP/DHCP VLAN; IEEE802.1X; OpenVPN; DSCP, 802.1p QoS > Time and Date synchronization: STNP, PBX, DHCP > Transport Feature: UDP/TCP/TLS; RTP/RTCP/SRTP	
Configuration & Maintenance		
Auto-provision	> TR069 (TR104/TR106) > FTP/TFTP/HTTPS for Auto Provisioning > Cloud device management: FACS > Cloud device management: FRPS > DHCP Option66	

Configuration	> Supports Web configuration > Reset to factory, reboot > Package tracing export, system log	
Others		
Physical Features	> New Stand, Wall mountable > AC/DC Adapter, AC Input: 100~240V, 50~60Hz > DC Output: 5V, 1A > Power consumption(PSU): 0.87~1.18W > Power consumption(PoE): 0.72~1.78W > Relative humidity: 10%~90% (No Condensing) - Storage temperature: -25~65°C - Operation temperature: 0~45°C > Dimension (W x D x H): 200mm x 165mm x 47mm	
Package Content		
Detials	Packing List:  > Flying Voice P10/P10P IP Phone、Power adapter (optional)  > Handset with handset cord, Ethernet cable, Stand  > Quick Start Guide  Size:  > Qty/CTN: 10 PCS、N.W/CTN: 7.5 kg、G.W/CTN: 9.47 kg  > Giftbox size: 288×217mm×60mm  > Carton size: 448mm×320mm×302mm	
Certification & Compatibility		
Certificated by	CEF© rőhs	
Compatible with	30X. Sproadsoft Asterisk	







## **About Flyingvoice**

Flyingvoice is a leading manufacturer of VoIP phones, ATA& gateways and VoIP routers. These products are preferred globally by international carriers, ITSP's, ISP's, corporate companies, and home users alike.

Driven by a need for ongoing innovation within VoWLAN technologies, Flyingvoice is committed to manufacturing products that allow for ease-of-installation scenarios within an enterprise network. Our people continuously improve existing products as well as expand upon product applications tailored to clients' requirements. These improvements ensure that your experience provides for secure, effective and efficient collaboration – anytime & anywhere.

### Copyright

Copyright © Flyingvoice Network Technology Co., Ltd. All rights reserved. No parts of this publication may be reproduced or transmit- ted in any form or by any means, electronic or mechanical, photocopying, recording, or otherwise, for any purpose, without the express written permission of Flyingvoice Network Technology Co., Ltd.

## **Technical Support**

Visit www.flyingvoice.com for product documents and FAQ, or contact Flyingvoice by email at support@flyingvoice.com. We'll get you the help you need.



Flyingvoice Network Technology Co., Ltd.

Website: www.flyingvoice.com

Add: 1801-1802, Building 1, Chongwen Park, Nanshan Zhiyuan,

Nanshan District, Shenzhen, China

Copyright© Flyingvoice Network Technology Co., Ltd. All Rights Reserved